DATASHEET



20L MILITARY FUEL CAN

- With UN packaging authorization for packing groups I, II and III (marking letter X)
- Made of 0,9mm hot-dip aluminium-silicon (AS) coated steel (min 50 g/m2)
- High durability external powder covering (min 70µm)
- Standard colour: Army green RAL6031
- Fuel resistant internal coating (min. 30µm)
- Cans are regularly tested and comply with Internal pressure test up to 2,5 bar and drop test from 1,8 m height

Additional options:

- Available special markings
- Available separate accessories: pouring spouts, adapters
- Colours are available on request according to army's specification
- Filled with aluminium foil mesh, which absorbs the heat and prevents explosion risk

SPECIFICATION	Fuel can	
Depth, mm	CFT/AFGOT165	
Width, mm	345	
Height, mm	468	
Net, kg	4,4	

SPECIFICATION	Box of 5	Box of 4
Pieces/box	0-1/25 COM	4
Depth, mm	854	678
Width, mm	358	358
Height, mm	488	488
Net, kg	22	17,6
Gross, kg	23	18,5

SPECIFICATION	Pallet	
Pieces/pll	75	56
Boxes/pll	15	14
Depth, m	1,2	1,2
Width, m	0,8	0,8
Height, m	2,60	2,49
Net, kg	330	246
Gross, kg	375	287









