## DATASHEET ARTICLE 82.00.00



## **20L METAL FUEL CAN**

- With UN packaging authorization for packing groups II and III (marking letter Y) and TÜV-mark type certification
- 0,9mm body metal thickness
- High durability external powder coating
- · Fuel resistant internal coating
- Wide breathing channel (pouring in less than 25 seconds)
- Cans are regularly tested and comply with Internal pressure test up to 1,0 bar and drop test from 1,2 m height

## Additional options:

- Available special markings
- Available separate accessories: pouring spouts, adapters, can holders.
- Colours are available on request according to RAL catalogue:



SPECIFICATION	Fuel can	
Depth, mm	D=YA.GOM 165 JULEYA.	
Width, mm	345	
Height, mm	468	
Net, kg	4,3	
A.Com J	D-TA.COM HJO-TA.	

SPECIFICATION	Box of 5	Box of 4
Pieces/box	5	4
Depth, mm	854	678
Width, mm	358	358
Height, mm	488	488
Net, kg	21,5	17,2
Gross, kg	23,1	18,4

SPECIFICATION Pieces/pll	Pallet	
	70	56
Boxes/pll	)_V/\_14	14
Depth, m	1,2	1,2
Width, m	0,85	0,85
Height, m	2,60	2,49
Net, kg	301	241
Gross, kg	348	283









